


PVP-2150

SPECIAL FEATURES

- * Application in LCD TV 32" (Samsung / LG)
- * Stable Output
- * Protection Circuit Built-in
- * Power Factor Correction
- * Built-in inrush current protection
- * Application products for ROHS
- * Built to meet FCC class B
- * Safety Approved : (CB : IEC60065)

ENVIRONMENTAL

- * Operating temperature range 0 to +45 deg.C.
- * Storage temperature range -20 to +70 deg.C.
- * Circuit is coated for protection against humidity



ELECTRICAL SPECIFICATION

1. Input Requirements

- Input Voltage Range : AC 90V ~ 264V
- Input Frequency Range : 47Hz ~ 63Hz
- Input Current Range : < 3.0A

2. Output Requirements

Output Name	Output Typical(V)	Variable Voltage Range(V)	Voltage Tolerance(%)	Output Current(A)	
				Min	Max
5VS	5	4.75VDC ~ 5.25VDC	±5	0.1	2.0
5VDD	5	4.75VDC ~ 5.25VDC	±5	1.0	5.0
12V	12	11.4VDC ~ 12.6VDC	±5	1.0	4.0
24V	24	22.8VDC ~ 25.2VDC	±5	1.0	5.5

DIMENSION

Size : 210mm X 130mm X 34mm

